

TEST CERTIFICATE

CT-21-04-26-02

Product: Type: Plywood
Characterisation: Beech plywood
Name of product: Multifine Beech
Date production: 30 March 2021

Company: DYAS.EU, a.s.
Veselská 384
687 24 Uherský Ostroh; Czech rep.

Order: Determination of the formaldehyde release following secondary test chamber method ASTM D6007-14

Test method: Test chamber method ASTM D6007-14
Chemical analysis: Acetylacetone - method
Limit of detection (LOD): 0.01 ppm

Test report: Test report 2521181 dated 26 April 2021

Test result: The formaldehyde release of the tested product is 0.05 ppm.

The tested sample meets the limit value for plywood (0.05 ppm) according to the requirements of EPA TSCA Title VI - 40 CFR Part 770 - Formaldehyde Standards for Composite Wood Products - § 770.10 (b)(1)-(4) "Formaldehyde emission standards" and CARB Phase 2 - Final Regulation Order of "ATCM to Reduce Formaldehyde Emission from Composite Wood Products" - §93120 - 93120.12, title 17, California Code of Regulations, § 93120.2 (a) "Formaldehyde Emission Standards for Hardwood Plywood (HWPW), particleboard (PB), and Medium Density Fiberboard (MDF)".

Dresden, 26 April 2021



Head of laboratory



Engineer in charge